



E-Z-GO® 2FIVE®

GO ON-ROADING.

Inspired and bold, sophisticated and fun. The E-Z-GO 2Five makes any journey more enjoyable. Balancing fun, convenience, safety and environmental responsibility, our first low speed vehicle (LSV) commands the attention of passers-by. It welcomes the notion that your day doesn't end at five and accommodates bags, groceries and the occasional science project. So take a seat behind the wheel and go on-riding in the invigorating E-Z-GO 2Five.

STANDARD FEATURES

- ▶ Dash-Mounted 12V Accessory Outlet
- ▶ Dash-Mounted Speedometer, Odometer & State of Charge Meter
- ▶ Three-point Seat Belts
- ▶ Automatic Parking Brake
- ▶ Passenger Side Locking Glove Box
- ▶ Turn Signals & Four-way Flashers
- ▶ Headlights & Taillights
- ▶ Brake Lights Including Center High Mount Light
- ▶ Driver & Passenger Side Mirror
- ▶ Automotive Safety Glass Windshield (AS1)
- ▶ Automotive-Style Rear View Mirror
- ▶ White OPS (Operator Protective Structure) Rated Canopy
- ▶ Floor Board-Mounted Horn
- ▶ DOT Street Legal 205-50-10 Radial



A Textron Company



2-PASSENGER

4-PASSENGER

DIMENSIONS

Overall Length	94.8 in (241 cm)
Overall Width	47.3 in (120 cm)
Overall Height	71.4 in (181 cm)
Overall Height (w/ strobe)	75.2 in (191 cm)
Wheel Base	65.9 in (167 cm)
Front Wheel Track	36.7 in (93 cm)
Rear Wheel Track	39.7 in (101 cm)
Ground Clearance @ Differential	4.7 in (12 cm)

Overall Length	107.1 in (272 cm)
Overall Width	47.3 in (120 cm)
Overall Height	71.2 in (181 cm)
Overall Height (w/ strobe)	75.2 in (191 cm)
Wheel Base	65.9 in (167 cm)
Front Wheel Track	36.7 in (93 cm)
Rear Wheel Track	39.7 in (101 cm)
Ground Clearance @ Differential	4.5 in (11 cm)

POWER

Power Source	48 Volt DC
Motor Type	48-volt AC
Horsepower (kW)	4.4 hp (3.3 kW) Continuous
Electrical System	48 Volt
Batteries (qty/type)	Six, 8-volt Deep-cycle
Battery Charger	On-board 48 VDC
Key or Pedal Start	Pedal
Speed Controller	235-amp AC Controller
Drivetrain	Motor Shaft Direct Drive
Transaxle	Helical Gears
Gear Selection	Dash-mounted Forward-Neutral-Reverse
Speed Selection	Dash-mounted High-Low Switch
Rear Axle Ratio	14.76:1 (Forward)
DC-DC Converter	30-amp Integrated Into On-board Charger

Power Source	48-volt DC
Motor Type	48-volt AC
Horsepower (kW)	4.4 hp (3.3 kW) Continuous
Electrical System	48 Volt
Batteries (qty/type)	Six, 8-volt Deep-cycle
Battery Charger	On-board 48 VDC
Key or Pedal Start	Pedal
Speed Controller	235-amp AC Controller
Drivetrain	Motor Shaft Direct Drive
Transaxle	Helical Gears
Gear Selection	Dash-mounted Forward-Neutral-Reverse
Speed Selection	Dash-mounted High-Low Switch
Rear Axle Ratio	14.76:1 (Forward)
DC-DC Converter	30-amp Integrated Into On-board Charger

PERFORMANCE

Seating Capacity	2-Passenger
Dry Weight (w/o batteries)	822 lb (373 kg)
Curb Weight	1150 lb (522 kg)
Vehicle Load Capacity	800 lb (363 kg)
Gross Axle Weight Rating (Front)	575 lb (261 kg)
Gross Axle Weight Rating (Rear)	2000 lb (907 kg)
Outside Clearance Circle	19.7 ft (6.0 m)
Speed – Low	14.0 mph (22.5 kph)
Speed – High	25.0 mph (40.2 kph)
Reverse Speed	8.0 mph (12.9 kph)

Seating Capacity	4-Passenger
Dry Weight (w/o batteries)	872 lb (396 kg)
Curb Weight	1200 lb (544 kg)
Vehicle Load Capacity	800 lb (363 kg)
Gross Axle Weight Rating (Front)	575 lb (261 kg)
Gross Axle Weight Rating (Rear)	2000 lb (907 kg)
Outside Clearance Circle	19.7 ft (6.0 m)
Speed – Low	14.0 mph (22.5 kph)
Speed – High	25.0 mph (40.2 kph)
Reverse Speed	8.0 mph (12.9 kph)

STEERING & SUSPENSION

Steering	Double-ended Rack and Pinion
Front Suspension	Independent A-arm with Coil Over Shock
Rear Suspension	Mono-leaf Springs with Hydraulic Shocks
Service Brake	Four-wheel Hydraulic Disc Brakes w/ Full-time Regenerative Braking
Parking Brake	Spring Applied Electro-Magnetic
Tires	DOT Street Legal 205-50-10 Radial

Steering	Double-ended Rack and Pinion
Front Suspension	Independent A-arm with Coil Over Shock
Rear Suspension	Mono-leaf Springs with Hydraulic Shocks
Service Brake	Four-wheel Hydraulic Disc Brakes w/ Full-time Regenerative Braking
Parking Brake	Spring Applied Electro-Magnetic
Tires	DOT Street Legal 205-50-10 Radial

BODY & CHASSIS

Frame	Welded steel w/ DuraShield™ Powder-Coat
Body & Finish	Injection Molded TPO and Automotive Style Paint
Available Body Colors	Almond, Barley Gold, Black, Bright White, British Racing Green, Burgundy, Electric Blue, Flame Red, Forest Green, Inferno Red, Ivory, Java Brown, Metallic Charcoal, Oasis Green, Patriot Blue, Platinum, Safety Yellow, Steel Blue, Sunburst Orange
Available Seat Colors	Stone Beige, Oyster
Pinstripe Colors	Pewter

Frame	Welded steel w/ DuraShield™ Powder-Coat
Body & Finish	Injection Molded TPO and Automotive Style Paint
Available Body Colors	Almond, Barley Gold, Black, Bright White, British Racing Green, Burgundy, Electric Blue, Flame Red, Forest Green, Inferno Red, Ivory, Java Brown, Metallic Charcoal, Oasis Green, Patriot Blue, Platinum, Safety Yellow, Steel Blue, Sunburst Orange
Available Seat Colors	Stone Beige, Oyster
Pinstripe Colors	Pewter



FRONT



BACK

POPULAR OPTIONS & ACCESSORIES

- ▶ Two-speed Windshield Wiper Kit
- ▶ Trunk Kit (Keyed to Match Glove Boxes)
- ▶ Battery Filling System with Nozzle
- ▶ Amber Strobe Light
- ▶ Lighted License Plate Holder
- ▶ Heater/Defroster
- ▶ Weather Enclosure
- ▶ Stereo Sound System with Speakers, Amplifier and MP3 Player Connectivity
- ▶ Sweater Basket/Golf Bag Rack



A Textron Company