# KATLER 800

### EXPERIENCE PROVEN PERFORMANCE.

The Hauler 800, now available with an ELiTE lithium powertrain activated by Samsung SDI battery technology or with a fuelefficient 13.5 hp EFI gas engine, gives you the power to accomplish any task on your course. With a fully customizable cargo bed, highly functional dash and a broad range of accessories, Hauler 800 vehicles have everything you need to finish job after job.

Les & Mars & Automation

CUSHMAN.COM

8.4 CU FT CARGO BED


I Town of the state of the

900LB Towing Capacity

800LB VEHICLE LOAD CAPACITY

2 PASSENGER SEATING

ZERO MAINTENANCE ELITE LITHIUM BATTERY







### **ELITE LITHIUM POWERTRAIN**

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range

### OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights High/Low Beam
- LED Taillights/Brake Lights
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Rear Receiver Hitch
- Hour Meter
- Rapid On-Board Charger (ELiTE Only)
- Fuel/Oil Gauge (Gas Only)

### CUSHMAN.COM

## HAULER<sup>®</sup> 800

**BODY & CHASSIS** 

HAULER 800 ELITE

HAULER 800 GAS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Forest Green

#### DIMENSIONS OVERALL LENGTH 110 in (279.4 cm) OVERALL WIDTH 49 in (125 cm) 47 in (119.4 cm) (No Canopy) OVERALL HEIGHT 69.5 in (176.5 cm) (w/ Struts & Roof) WHEEL BASE 65.5 in (166.4 cm) WHEEL TRACK 37 in (94 cm) Front / 38 in (96.5 cm) Rear GROUND CLEARANCE 4.3 in (10.9 cm) CARGO BOX CAPACITY 8.4 cu ft (0.24 m3) 28.5 in (L) x 44.5 in (W) x 12 in (D) CARGO BOX DIMENSIONS (72.4 cm x 113 cm x 30.5 cm) CARGO BOX MATERIAL Roto-Molded Polyethylene

### POWER

POWER TRAIN	56.7V Li-Ion Battery	4-Cycle, 24.5 ci (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	11.7 HP (8.7 kW) Peak	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	2.2 Elite - Single Pack	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash Mount Forward-Neutral- Reverse / Key Switch	Forward - Reverse
REAR AXLE RATIO	16.99:1	11.47: 1 (Forward) 14.35:1 (Reverse)

### PERFORMANCE

SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/O BATTERIES	753 lb (342 kg)	761 lb ( 345.2 kg)
CURB WEIGHT	800 lb (363 kg)	791 lb (359 kg)
VEHICLE LOAD CAPACITY	800 lb (362.9 kg)	
BED LOAD CAPACITY	400 lb (1	181.4 kg)
TOWING CAPACITY	900 lb (408.2 kg)	
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)

#### **STEERING & SUSPENSION**

STEERING	Self-Compensating Rack and Pinion		
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers		
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum		
PARKING BRAKE	Self-Compensating, Single-Point Engagement		
TIRES (FRONT & REAR)	18 x 8.5 -8 (6 Ply Rated)		

©2022 Textron Specialized Vehicles Inc. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

70030-G5 (Rev. 06/2022)

