

72-VOLT AC ELECTRIC OR 13.5-HP GAS ENGINE WITH CLOSED LOOP EFI

COMFORTABLE ROOM FOR 6 7 INCHES OF GROUND CLEARANCE TO EXPLORE OFF-ROAD

EXPRESS™ L6





ELECTRIC

ADD EVEN MORE TO YOUR LIFE.

Outdo yourself by exploring more than ever before with the Express L6 series. With room for 6, rugged tires, and higher ground clearance, you'll elevate everyone's expectations for a smooth, stylish ride. Boost your drive time with the unbeatable power of our exclusive 72-volt powertrain or choose the industry's first closed-loop EFI powertrain. It's time to start crossing things off your bucket list with the Express L6, here to awaken your sense of adventure.

KEY FEATURES

- Spacious legroom and front room operator area
- Smooth and quiet Paramount M/T Tires with Radial SPDR Wheel
- New Rear Facing Seat with Cup-holders
- · Functional dash with versatile cup and technology holders and three storage areas
- · Dashboard Storage Pockets
- · Premium Steering Wheel
- · Large Fender Flares
- · Dual USB Ports
- · Multi-Function Speed, State Of Charge and Hour Meter Gauge (Electric Only)
- DC/DC Converter (Electric Only)
- · 72-Volt AC Powertrain (Electric Only)
- Fuel Gauge (Gas Only)
- · Low Oil Indicator (Gas Only)

DIMENSIONS	
OVERALL LENGTH	144 in (364 cm)
OVERALL WIDTH	49 in (125 cm)
OVERALL HEIGHT (W/O ROOF)	55.5 in (141 cm)
OVERALL HEIGHT (W/ ROOF)	83 in (211 cm)
WHEEL BASE	97 in (245 cm)
FRONT WHEEL TRACK	38.5 in (98 cm)
REAR WHEEL TRACK	38.5 in (98 cm)
GROUND CLEARANCE @ DIFFERENTIAL	7.0 in (18 cm)

POWER

_....

VALVE TRAIN N/A Single C MOTOR TYPE AC Induction FUEL SYSTEM N/A Closed-Loop Ele HORSEPOWER (KW) 22.4 hp (16.7 kW) Peak 13.5 hp (10.1 kW) E ELECTRICAL SYSTEM 72 Volt Starter/Generator BATTERIES (QTY/TYPE) Six, 12 Volt Deep Cycle One, 12 Volt N	5 cu in (401 cc) tylinder OHV N/A ctronic Fuel Injection xceeds SAE J1940 Std - Solid State Regulator	
MOTOR TYPE AC Induction FUEL SYSTEM N/A Closed-Loop Ele HORSEPOWER (KW) 22.4 hp (16.7 kW) Peak 13.5 hp (10.1 kW) Ele ELECTRICAL SYSTEM 72 Volt Starter/Generator BATTERIES (QTY/TYPE) Six, 12 Volt Deep Cycle One, 12 Volt M	N/A ctronic Fuel Injection xceeds SAE J1940 Std	
FUEL SYSTEM N/A Closed-Loop Ele HORSEPOWER (KW) 22.4 hp (16.7 kW) Peak 13.5 hp (10.1 kW) Ele ELECTRICAL SYSTEM 72 Volt Starter/Generator BATTERIES (QTY/TYPE) Six, 12 Volt Deep Cycle One, 12 Volt M	ctronic Fuel Injection xceeds SAE J1940 Std	
HORSEPOWER (KW) 22.4 hp (16.7 kW) Peak 13.5 hp (10.1 kW) Examples ELECTRICAL SYSTEM 72 Volt Starter/Generator BATTERIES (QTY/TYPE) Six, 12 Volt Deep Cycle One, 12 Volt M	xceeds SAE J1940 Std	
BATTERIES (QTY/TYPE) Six, 12 Volt Deep Cycle One, 12 Volt M		
BATTERIES (QTY/TYPE) Six, 12 Volt Deep Cycle One, 12 Volt M	- Solid State Regulator	
WEY OR REPAIR CTART	Maintenance Free	
KEY OR PEDAL START Pedal Start		
AIR CLEANER N/A Replaceabl	e Dry Cartridge	
LUBRICATION N/A Pressurize	ed Oil System	
OIL FILTER N/A Sp	oin-On	
COOLING SYSTEM N/A Air	Cooled	
FUEL CAPACITY N/A 5.96 Gallor	n (22.6 L) Tank	
BATTERY CHARGER 72V, 120/230 VAC, UL & CSA	N/A	
SPEED CONTROLLER 350 Amp AC	N/A	
DRIVETRAIN Motor Shaft Direct Drive Continuously Variation	ble Transmission (CVT)	
TRANSAXLE Differential with Helical Gears	Differential with Helical Gears	
GEAR SELECTION Dash Mounted Forward-Neutral-Reverse Forward	rd-Reverse	
REAR AXLE RATIO 17:1 11.47:1 (Forward	i); 14.35:1 (Reverse)	

PERFORMANCE

SEATING CAPACITY	6-Pas	ssenger
DRY WEIGHT	1066 lb. (484 kg)	1150 lb (522 kg) (without battery)
CURB WEIGHT	1558 lb. (707 kg)	1190 lb (540 kg)
VEHICLE LOAD CAPACITY	1200 lb	(544 kg)
OUTSIDE CLEARANCE CIRCLE	28.8 ft	t (7.8m)
SPEED (LEVEL GROUND)	Up to 19 mph \pm 0.5 mph (Up to 30.6 kph ± 0.8 kph)

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single Point Engagement
TIRES	MT Paramount, 23x10-14, Radial, SPDR Alloy Wheel

BODY & CHASSIS

FRAME	Welded steel with E-coat and DuraShield™ powder coat
BODY & FINISH	Injection Molded TPO
AVAILABLE BODY COLORS	Black, Bright White, Electric Blue, Flame Red, Inferno Red, Metallic Charcoal, Ocean Grey, Platinum, Slate
AVAILABLE SEAT COLORS	Black, Grey on Black, White on Beige
AVAILABLE PREMIUM SEAT COLORS	Black, Grey, Mushroom







©2021 Textron Specialized Vehicles Inc. 82455-G16 (Rev. 07/2021)











Platinum







www.ezgo.com





MAINTENANCE FREE BATTERIES

8-YEAR BATTERY WARRANTY

UNBEATABLE ENERGY EFFICIENCY

EXPRESS™ L6 ELITE™



THE LUXURY OF HAVING MORE.

The Express L6 ELiTE is fully loaded with technology like no other. Powered by a high performing, energy efficient Samsung SDI lithium battery system, the Express L6 ELiTE will ignite your next adventure. With maintenance free batteries, backed by an unprecedented 8-year battery warranty, the Express L6 ELiTE helps cultivate the perfect memories making the most of every moment. It's time to get away, time to explore and see what adventures you can find along the next path. The perfect spot is waiting to be found with the Express L6 ELITE.

TECHNOLOGY LIKE NO OTHER

- · Zero-Maintenance Batteries
- · Unprecedented, Industry Leading 8-Year Warranty
- Proven Technology w/ Samsung SDI Lithium Batteries
- · Effortless Energy Efficiency
- · Unbeatable Performance
- · Eco-Friendly Technology

KEY FEATURES

- · Spacious learoom and front room operator area
- · Smooth and quiet Paramount M/T Tires with Radial SPDR Wheel
- · New Rear Facing Seat with Cup-
- · LED Headlights, Taillights and Brake
- · Functional dash with versatile cup and technology holders and three storage areas
- · Large Fender Flares
- · Premium Steering Wheel
- · Dual USB Ports

DIMENSIONS	
OVERALL LENGTH	144.5 in (367 cm)
OVERALL WIDTH	49 in (125 cm)
OVERALL HEIGHT (W/O ROOF)	56 in (142 cm) (Top of steering wheel)
OVERALL HEIGHT (W/ ROOF)	80 in (203 cm)
WHEEL BASE	99.5 in (253 cm)
FRONT WHEEL TRACK	38.5 in (98 cm)
REAR WHEEL TRACK	38.5 in (98 cm)
GROUND CLEARANCE © DIFFERENTIAL	5.5 in (14 cm)

POWER	
POWER SOURCE	56 Volt DC
MOTOR TYPE	56 Volt AC
HORSEPOWER (KW)	13.1 HP (9.8 kW) Peak
ELECTRICAL SYSTEM	56 Volt
BATTERIES (TYPE)	Three Lithium Ion 56 Volt
KEY OR PEDAL START	Pedal Start
BATTERY CHARGER	56VDC, 120/230 VAC, UL/CSA, CE
SPEED CONTROLLER	300 Amp AC
DRIVETRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential with Helical Gears
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	17:1

PERFORMANCE	
SEATING CAPACITY	6-Passenger
DRY WEIGHT	1125 lb (510 kg) (without battery)
CURB WEIGHT	1225 lb (556 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)
HIGH SPEED (LEVEL GROUND)	Up to 19 mph \pm 0.5 mph (Up to 30.6 kph \pm 0.8 kph)

STEERING & SUSPENSION	
STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single Point Engagement
TIRES	MT Paramount, 23x10-14, Radial, SPDR Alloy Wheel

TIRES	MT Paramount, 23x10-14, Radial, SPDR Alloy Wheel
BODY & CHASSIS	
FRAME	Welded Steel with E-coat & DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
AVAILABLE BODY COLORS	Black, Bright White, Electric Blue, Flame Red, Inferno Red, Metallic Charcoal, Ocean Grey, Platinum, Slate
AVAILABLE SEAT COLORS	Black, Grey on Black, White on Beige
AVAILABLE PREMIUM SEAT COLORS	Black, Gray and Mushroom







©2020 Textron Specialized Vehicles Inc. 82666-G4 (Rev. 12/2020)









Ocean Grey



Platinum









